

**DOG HOLLOW SPEEDWAY**  
**OFFICIAL 2017 SUPER LATE MODEL RULES**

**1. FRAME**

- Only manufactured Late Model Frames allowed.
- Must have full floor boards and firewall in driver's compartment.

**2. SUSPENSION**

- Any suspension allowed.

**3. STEERING**

- Any steering allowed - (Except **NO** center steering.)

**4. SHOCKS**

- Any shocks allowed.

**5. WHEELS**

- Any wheel allowed – (Mounted with lug nuts.)

**6. TIRES**

- Any tire 1100 series.

**7. WHEELBASE**

- 103" minimum.

**8. CARBURETOR**

- Any carburetor allowed.

**9. ENGINE SETBACK**

- 6" maximum. Measured from furthest forward spark plug to center of upper ball joint.

**10. REAR-END**

- Any rear end allowed.

## **11. TRANSMISSION**

- Any transmission allowed. Must have working reverse.

## **12. STARTER**

- Cars must start and run under their own power.

## **13. CLUTCH**

- Any clutch allowed.

## **14. ENGINE**

- No cubic inch max.
- Oil dry sumps allowed.
- No turbo or superchargers. No nitrous oxide.
- Gas or Alcohol.

## **15. WEIGHT**

- **2,275 lbs.** minimum weight for Aluminum engine with the driver after feature.
  - Maximum Vertical Spoiler Height: **8 Inches.**
- **2,275 lbs.** minimum weight for Steel Block engine with the driver after feature.
  - Maximum Vertical Spoiler Height: **10 Inches.**
- **2,150 lbs.** minimum weight for GM CT525 engine with the driver after feature.
  - Maximum Vertical Spoiler Height: **12 Inches.**

## **16. WEIGHT / BALLAST**

- Weights up to 50 lbs must be positively fastened by 2 ½-inch, minimum grade 5 bolts with a minimum of two (2) weight clamps. Threaded rods will not be permitted. All weights must be painted white and clearly labeled with the car number on it.
- Any weight(s) must be securely attached to the frame below the body decking.
- Any car that loses any weight/ballast during an event may be subject to a penalty.
- Weights attached to the rear bumper and/or outside the frame will not be permitted.
- Pellet-type and/or liquid-type weight/ballast will not be permitted.
- Driver operated weight adjustment, 'weight jacking' devices will not be permitted.

## **17. BODIES**

- See attached body diagram.

All body panels must be solid - no holes, gaps, slots, etc!

Side spoiler specifications - max. 3 side spoilers. Max length at top - Unlimited 6", Spec 10", GM 525 14".  
Must taper down evenly! May be triangular or curved.

Roof supports must meet rear deck as shown. Max. 17" at top of roof supports.

Spillboards may have 1" ridge running at 90 degree angle on top.  
Spec - 1 spillboard, max. 4" high x 32" long,  
GM 525 - 1 spillboard, max. 4" high x 36" long,  
Unlimited - not permitted.

