

# ***DOG HOLLOW*** *Speedway*

## **OFFICIAL 2018 358 SEMI LATE RULES**

### **1. CHASSIS/BODY**

- Late model chassis permitted, 103 wheelbase minimum.
- **NO** glass permitted!
- Aluminum or rubber nose permitted.
- Full floorboards and fire walls in drivers compartment.
- **NO** sideboards or wings permitted!
- Maximum deck height 38 inches.
- Maximum spoiler height 8 inches.
  - **Any car running a 602 Crate Motor will be allowed a 12 inch spoiler. Only applies at Dog Hollow Speedway & Roaring Knob Speedway!**
- Maximum length of spoiler sides or center support 18 inches.
- Maximum deck height with spoiler 46 inches.
- **No part of the body or frame will be longer than 46 inches from the center of the rear wheels to the rear of the car.**
- All cars must have tow hooks or cables clearly visible.

### **2. SUSPENSION/DRIVELINE**

- Any suspension permitted.
- Fixed valve shock only, **NO** adjustable shocks of any kind anywhere.
- **NO Schraeder Valves, no exceptions!**
- Quick change or 9 inch permitted.
- Transmission may be standard, automatic or internal clutch racing. Reverse must be in working order.
- **Non-race type transmissions must have protective bell housing.**

### **3. WEIGHT**

- 2400lbs with driver after Heats and Feature.
  - 2200lbs with GM 602 crate with driver after Heats and Feature.
- **All added weight must be bolted securely inside the frame!**
- No weight may be inside the drivers compartment.
- All weight must be painted white with the car number clearly marked on them.

# **DOG HOLLOW** *Speedway*

## **4. ENGINE**

- **NO** aluminum blocks.
- Factory cast iron blocks or sealed GM 602 Crate engine, no aftermarket blocks. Cars with GM 602 must be clearly marked at the bottom of the driver's window.
- Cast Iron Heads **ONLY!** **NO** aluminum heads! Only factory valve stem angle. Example: Chevrolet is 23 degrees.
- **NO dry sump oiling systems or components of any type.**
- 2 or 4 barrel carburetors gasoline or alcohol.
- Maximum spacer / adapter height 2 inch total.
- **NO** turbos or super chargers!
- **NO** fuel injection!
- **NO** nitrous!
- 360 cubic inch limit. Engine block must be factory 360 cubic inch or smaller. Example: **NO** GM 400 block with a 327 crankshaft! We will be using casting numbers to check this!
- **Missing casting numbers or altered numbers will be grounds for disqualification and possible suspension! NO EXCEPTIONS!**
- Maximum cam lift is .515 intake and exhaust measured at the valve as raced!
- **NO** roller cams or lifters! Roller rockers are permitted.
- **OEM stock stroke crankshaft only.**
- Flat top pistons only.
- All exhaust must exit the car.
- All cars must start and run under their own power.
- **Must have 12-volt starting system.**

## **5. WHEELS AND TIRES**

- Steel and aluminum wheels only!
- Any tire, 1100 series max.

### **PLEASE NOTE:**

- Drivers may not race in any other Late Model class the same night they are running in the 358 Semi Late class!\*
- Illegal parts will be confiscated and not returned!